

## GPS Disciplined Rubidium Frequency & Time Reference

### Features

- Sine wave or CMOS/TTL output
- Short term stability  $2 \times 10^{-12}$  at 100sec
- Accuracy to 25ns RMS UTC
- Ultra Low phase noise -115dBc at 1Hz
- National & International Traceable Reference consumption



### Description

The E8010 provides a stable and accurate calibration free GPS time & frequency with multiple outputs signal formats in an easy to install 1U rack mountable chassis. This reference maintains high time and frequency accuracy required for demanding applications.

The added advantage of the internal rubidium module is that there is no measurable difference between the stability when locked to GPS or in Holdover mode with measurement times up to 1000s.

### Applications

- $1 \times 10^{-12}$  frequency accuracy
- No Drift
- 50ns 1PPS accuracy to UTC
- RS232 NMEA NTP Time Reference
- Alternative Cesium
- No Calibration
- Excellent holdover performance up to measurement time up to 1000s
- National & International traceable reference
- Microwave Test Bench or Test solution

### Related products

- **E8000**: 1U 19" rack mount up to 12 output, frequencies 1 to 100MHz
- **E80-GPS**: Low Noise Desktop & Bench top Frequency reference 1 to 4 outputs
- **E8-Y**: Low cost and Low Noise Desktop Frequency reference 1 to 4 outputs
- **E8-X**: Low cost Desktop Frequency reference 1 to 4 outputs

## E8010 Specification

### Outputs *See options*

10MHz	+8dBm ( $\pm 2$ dBm) into 50 Ohms, 0.7V <sub>rms</sub> (Specify for 75Ω load)
Connector	BNC standard (SMA available)

### Frequency Stability *Allan Deviation*

	Options A	Options B	Options C
Frequency	10MHz	10MHz	10MHz
$\tau = 1s$	$\leq 1 \times 10^{-11}$	$\leq 2 \times 10^{-13}$	$\leq 8 \times 10^{-13}$
$\tau = 10s$	$\leq 5 \times 10^{-11}$	$\leq 4 \times 10^{-12}$	$\leq 2 \times 10^{-12}$
$\tau = 100s$	$\leq 2 \times 10^{-11}$	$\leq 6 \times 10^{-12}$	$\leq 4 \times 10^{-12}$

### Phase Noise (SSB)

	Options 1	Options 2	Options 3	Options 3
Frequency	10MHz	10MHz	10MHz	10MHz
1Hz	-67 dBc	-100 dBc	-110 dBc	-115 dBc
1Hz	-95 dBc	-125 dBc	-136 dBc	-140 dBc
100Hz	-127 dBc	-145 dBc	-150 dBc	-154 dBc
1 kHz	-145 dBc	-150 dBc	-155 dBc	-155 dBc
10KHz	-144 dBc	-155 dBc	-157 dBc	-160 dBc

### Harmonics

	Standard	Options C
	<-30dBc	<-45dBc

### Spurious

	Standard	Options C
100 KHz BW	<-100dBc	<-100dBc

### 1PPS Output

Accuracy	<+12ns
Pulse Width	10 millisecond
Output level	CMOS 0-3.3V

### Holdover

Per 24 hours	1μ sec.
--------------	---------

### Warm-up time

<30 minutes, time to lock at room temperature 25°C

### Environmental

Temperature :	Operating	-40°C +60°C
	Storage	-40°C +90°C
Temp stability :	-20°C +60°C	0.1x10 <sup>-9</sup>

Relative humidity : 92% non-condensing

Magnetic Field sensitivity : 2x10<sup>-11</sup> Gauss

Atmospheric pressure : 1x10<sup>-13</sup> Per mbar

Approximate MTBF : 100,000 Hrs, Stationary

Dimensions without cover 44 x 250 x 444mm LWH

### Power supply

AC power: 90 – 240V

Power consumption: 22W Max at start (25°C)  
6W at steady state

### Data output & monitoring Options D

RS232, 9600 baud rate USB Ethernet

NMEA output sentences: GPGLL, GPGGA, GPGSA, GPGSV & GPRMC

GPS receiver data output in TSIP format.

Processor data include unit status.

### Built-in options

- Option 01:** Redundant switchover for external power back-up
- Option 02:** Output 2048kHz
- Option 03:** Output 1544kHz
- Option 04:** 13MHz Output
- Option 05:** TTL Output
- Option 07:** 10.24MHz Output
- Option 08:** 10.23MHz Output
- Option 09:** Add 6 Output Distribution Card
- Option 10:** 26MHz Output
- Option 18:** Extended warranty to 3 years
- Option 20:** Discipline to external GPS 1PPS or 10MHz input
- Option 42:** Low noise floor -170dBc at 10KHz
- Option 52:** Rack Mount 19" 2U
- Option 62:** AC Input 110V
- Option 64:** DC input: Specify +12V, +24V, +48V or +60V
- Option 75:** Add internal battery, up to 4 hours of battery life.

**Included with shipment:** Calibration certificate, Certificate of Conformance, product test sheet and 24 month warranty.

Contact us to configure this product to meet your requirement.  
Designed and manufactured in the U.K.

## Typical configuration

The E8010 can be configured to any frequencies from 1 to 100MHz of your preferred signal format. Standard connectors are BNC and SMA but E8010 can be configured with any output connector to suit your application.



## Included with the shipment

All Quartzlock GPS frequency references are supplied with our **standard GPS Antenna, Manual, Test sheet, Calibration certificate and Certificate of conformance.**



Standard GPS antenna with 5 meters of cable

## Optional upgrade

The High Gain GPS Antenna is designed for stationary application and all weather and harsh environment to provide a strong signal. This antenna is also a high-quality solution for adding GPS RF signals to marine GPS navigation systems. The high gain GPS antenna can be setup with up to 70 meters of cable. The high gain GPS antenna is supplied with stainless steel antenna mount.



High Gain GPS antenna

### High Gain GPS Antenna specifications:

Waterproof, weatherproof  
Operating Temp -40°C to +85°C  
Gain: 35dB ±3dB  
Voltage: +5V  
Connector: TNC  
L1 GPS, 1575.42MHz ±1.023MHz  
ROHS compliant



Antenna mount & coaxial cable